boyd acoustic

Floating Ceiling Panel Installation Instructions

Please note these Installation Instructions are the same for the Boyd Acoustic Round or Square Floating Ceiling Panels.

- 1. On the ceiling mark out where your Floating Ceiling Panel mounts need to go. Ensure your marks are in a square shape with the width of the square the same width as the bars installed on your Floating Ceiling Panel. This will ensure the wires hang straight once installed.
- 2. To install the Ceiling Fixings (1) cut 4 equal lengths of wire based on the gap you need between the ceiling and the Floating Ceiling Panel. Insert the 4 wires into the Ceiling Fixings and tighten the supplied crimp around the wire to secure the end as shown (2).
- 3. Take the other end of the wire and feed it into the Panel Fixing ③ as shown. Secure the wire using an allen key (not provided). Screw the Panel Fixing back together and repeat for all 4 wires. You should now have 4 wires hanging with Panel Fixings connected.
- 4. Use 2 people to lift the Floating Ceiling Panel up to the ceiling and slide the Panel Fixings into the installed channel on the ceiling. Repeat for all 4 wires.
- 5. Check that the Floating Ceiling Panel is sitting flat and that all 4 wires hang straight. Adjust by sliding the Panel Fixing along the channel where necessary.
- 6. Screw the base of the Panel Fixing (4) down into the channel to lock it in place.
- 7. Once installed small adjustments can be made to the length of the wire by tightening or loosening the top of the Panel Fixing (5).



Please contact your Boyd Account Manager E sales@boydworkspaces.co.nz for more information or call our friendly team on 09 271 2020.

